

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Hykomol LS 85W-90 limited slip gear oil

Version: 4 Latest revision: 06. 10. 2015 Date of issue: 20. 06. 2007 Page: 1/(13)

Section 1 Identification of the mixture and of the company/undertaking

1.1 Product identifier:

MOL Hykomol LS 85W-90 limited slip gear oil

1.2 Relevant identified uses of the mixture and uses advised against

Relevant identified uses: gear oil Uses advised against: no data

1.3 Details of the supplier of the safety data sheet:

MOL-LUB Lubricant Production Trade and Service Limited Liability Company

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 34 526 330 / +36 34 526 391

E-mail: kenoanyag@mol.hu

Request SDS of:

MOL-LUB Lubricant Production Trade and Service Limited Liability Company

Customer Service Center

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 80 201 296 / +36 34 348 010

Responsible for SDS:

MOL-LUB Ltd. Csaba Horváth, head of SD, HSE & Business Support

Phone: +36 34 526 343; Mobile: +36 20 474 2644

e-mail: csahorvath@mol.hu

1.4 Emergency telephone number

Emergency telephone (on workdays: 07-15²⁰ h (CET)): +36 34 526 210

Health Toxicological Information Service (ETTSZ 1096 Budapest, Nagyvárad tér 2.)

Tel.: +36 1 476 6464, or +36 80 201 199

National Health Toxicological Information Service:





Trade name: MOL Hykomol LS 85W-90 limited slip gear oil

Version: 4 Latest revision: 06. 10. 2015 Date of issue: 20. 06. 2007 Page: 2/(13)

Section 2 Hazards identification

2.1 Classification of the mixture

Hazard Class and Category: Hazard statement:

Skin Sens. 1 H317 May cause an allergic skin reaction.

Eye Dam. 1 H318 Causes serious eye damage.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting

effects.

2.2 Label elements ((EC) No 1272/2008)

Product identification: Trade name: MOL Hykomol LS 85W-90 limited slip gear oil

Hazardous component: Reaction products of bis(4- methylpentan-2-yl)dithiophosphoric

acid with phosphorus oxide, propylene oxide and amines, C12-14

alkyl(branched) (EU: 931-384-6) Oleilamin (CAS Nr.: 112-90-3)

Reaction product of 1,3,4- thiadiazolidine-2,5- dithione, formaldehyde and phenol, heptyl derivs (EU Nr.: 939-460-0)

GHS Pictogram:

Signal word: **Danger**

Hazard statement:

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

Supplemental hazard information:

EUH208 Contains reaction product of 1,3,4-thiadiazolidine-2,5-dithione,

formaldehyde and phenol, heptyl derivs. May produce an allergic

reaction.

Precautionary statements - General: -

Precautionary statements – Prevention:

P273 Avoid release to the environment.

P280 Wear protective gloves, protective clothing, eye protection/face

protection.





Trade name: MOL Hykomol LS 85W-90 limited slip gear oil

Version: 4 Latest revision: 06. 10. 2015 Date of issue: 20. 06. 2007 Page: 3/(13)

Precautionary statements – Response:

P333-+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

Precautionary statements – Storage: -Precautionary statements – Disposal:

P501 Dispose of contents/container in accordance with national

regulation.

Other liabilities for labelling:

Tactile warning of danger: Not required. Transport classification: see section 14.

2.3 Other hazards

The product does not contain any PBT or vPvB substance according to annex XIII of regulation (EC) 1907/2006.

Section 3 Composition/information on ingredients

3.2 Mixtures

Chemical description: Mixture of refined mineral base oils containing additives.

Component(s) / Hazardous component(s):

Name	EU	CAS	Hazard classes and	Hazard	Conc.
Name	number	number	cat.	statements	%(m/m)
Lubricating oils (petroleum),	309-874-0	101316-69-2	=	-	max. 85
C>25*			(Note L)		
REACH Registr.Nr.:					
01-2119486948-13					
Lubricating oils (petroleum),	309-877-7	101316-72-7	Asp. Tox. 1	H304	max. 25
C24-C50*			(Note L)		
REACH Registr. Nr.:					
01-2119489969-06					
Refined petroleum		confidential	-	-	max. 10
distillate, mixtures *(**)			(Note L)		
Reaction products of bis(4-	931-384-6	-	Acute Tox. 4	H302	max. 2
methylpentan-2- yl)			Eye Dam. 1	H318	
dithiophosphoric acid with			Skin Sens. 1	H317	
phosphorous oxide, propylene			Aquatic Chronic 2	H411	
oxide and amines, C12-C14					
alkyl(branched)					
REACH Registr.Nr.:					
01-2119493620-38					



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Hykomol LS 85W-90 limited slip gear oil

Version: 4 Latest revision: 06. 10. 2015 Date of issue: 20. 06. 2007 Page: 4/(13)

Name	EU	CAS	Hazard classes	Hazard	Conc.
	number	number	and cat.	statements	%(m/m)
Reaction Products of alcohols, C14-18, C18 unsat., esterified with phosphorus pentoxide and salted with amines, C12- 14,-tert-alkyl REACH Registr. Nr.: 01-2119978530-33	939-591-3	-	Aquatic Chronic 3	H412	max. 1.5
Oleilamin	204-015-5	112-90-3	Acute Tox. 4 Asp. Tox. 1 Eye Dam. 1 Skin Corr. 1C STOT SE 3 STOT RE 2 Aquatic Acute 1 Aquatic Chronic 1	H302 H304 H318 H314 H335 H373 H400 H410	max. 0.65
Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs. REACH Registr. Nr.: 01-2119971727-23	939-460-0	-	Flam Liq. 3 Eye Dam. 1 Skin Irrit. 2 Skin Sens. 1 Aquatic Chronic 3	H226 H318 H315 H317 H412	max. 0.6.

^{*:} with exposure limit

(**) The EU Numbers of mixture: 265-157-1, 265-169-7, 265-158-7, 265-159-2

The full text of each relevant H-phrase, Hazard classes and cat. see in Section 16.

Section 4 First aid measures

4.1 Description of first aid measures

General information: Never give anything by mouth to an unconscious person, or never

induce vomiting.

Inhalation: Remove the affected person to fresh air. If rapid recovery does not occur,

obtain medical attention.

Skin Remove contaminated clothing. Wash skin with large amounts of water, use

contact: soap. In case of persistent irritation, get medical attention.

Eye contact: Flush eyes with plenty of water for 10-15 minutes. In case of persistent

irritation, get medical attention.

Ingestion: If swallowed, give water. Do not induce vomiting. Get medical attention.

Protection of first-aid person: No individual specifications.

4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

Causes serious eye damage.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Hykomol LS 85W-90 limited slip gear oil

Version: 4 Latest revision: 06. 10. 2015 Date of issue: 20. 06. 2007 Page: 5/(13)

4.3 Indication of any immediate medical attention and special treatment need Not required.

Section 5 Fire-fighting measures

Fire hazards:

Combustible

5.1 Extinguishing media

Suitable extinguishing media:

Foam, carbon dioxide, dry chemical powder.

Unsuitable extinguishing media:

Water jet.

5.2 Special hazards arising from the mixture

Hazardous combustion products:

On burning, carbon dioxide, carbon monoxide, sulphur oxides, nitrogen oxides, phosphor oxides, various hydrocarbons and soot can be formed.

5.3 Advice for fire-fighters

Special protective equipment:

According to the existing fire-fighting regulations, respiratory protection.

Further information:

Collect contaminated fire fighting water separately. It must not enter the sewage system. Contaminated extinguishing water must be disposed of in accordance with official regulations.

Section 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Personal precautions: see Section 8.

6.2 Environmental precautions:

Confine spills to prevent material from entering sewers, watercourses, drains and into soil Notify relevant authority.

6.3 Methods and material for containment and cleaning up

On soil: All kind of ignition sources should be remove. Recover free liquid by

pumping. Contain the rest or small quantities with sand, earth or other

suitable absorbents. Dispose of according to local regulations.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Hykomol LS 85W-90 limited slip gear oil

Version: 4 Latest revision: 06. 10. 2015 Date of issue: 20. 06. 2007 Page: 6/(13)

On water: Confine the spillage. Remove from surface by skimming or suitable

absorbents. Notify local authorities according to regulations.

6.4 Reference to other sections

Personal precautions: see section 8.

Waste treatment methods: see section 13.

Section 7 Handling and storage

7.1 Precautions for safe handling

Keep general measures applied for normal operations with lubricants and flammable liquids.

Keep away from radiant heat and open flame.

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or mists.

Ensure washing facilities after working hours and before breaks. Take off contaminated or oil-soaked clothing, wash with warm water and soap.

When using do not eat, drink or smoke. Avoid splashing the product.

Handling temperature: not known

7.2 Conditions for safe storage, including any incompatibilities

Storage facilities must comply with regulations for storing of flammable liquids.

Store in dry, well ventilated place in original, closed containers.

Keep away from radiant heat, open flame and strong oxidizing agents.

Storage temperature: max. 40°C

7.3 Specific end use(s)

Gear oil.

Section 8 Exposure controls / personal protection

Engineering control measures:

Not required.

8.1 Control parameters:

Mineral oil mist: TWA: 5 mg/m³; STEL: 10 mg/m³, for oil mist, vapour

excluded (ACGIH).

Method of testing, recommended: NIOSH 5026

8.2 Exposure controls

Personal protection:

Respiratory protection: Breathing apparatus not required.





Trade name: MOL Hykomol LS 85W-90 limited slip gear oil

Version: 4 Latest revision: 06. 10. 2015 Date of issue: 20. 06. 2007 Page: 7/(13)

Hand protection: Oil resistant gloves (EN 374, Breakthrough time 480 min)

(e.g. nitrile rubber – minimal thickness 0.33 mm).

Note: Manufacturer's directions for use and the conditions of

application should be observed.

Eye protection: Where splashing is possible, wear safety glasses with side

shields.

Skin protection: Protective clothing (oil resistant).

Other special: no data

Environmental exposure controls:

Do not discharge into drains/surface waters/groundwater.

Section 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:

Physical state: liquid

Colour: brown, clear Odour: characteristic

Change in physical state:

Pour point (ISO 3016): typ. -27°C Boiling point (DIN 51356): not available

Others:

Flash point (COC) (EN ISO 2592): typ. 220°C Ignition point (EN ISO 2592): not available Autoignition temperature: not available Explosive properties: not explosive Oxidizing properties: not oxidize Vapour pressure at 20°C: negligible

Density at 15° C (EN ISO 12185): $0.895 - 0.915 \text{ g/cm}^3$

Solubility in water: practically insoluble in water Solubility in other solvents: gasoline, kerosene, toluene, etc.

n-Octanol/water partition coefficient:

Vapour density:

Evaporation rate:

Heating value:

Kinematic viscosity at 40°C (EN ISO 3104):

Kinematic viscosity at 100°C (EN ISO 3104):

typ. 204.7 mm²/s

typ. 17.1 mm²/s





Trade name: MOL Hykomol LS 85W-90 limited slip gear oil

Version: 4 Latest revision: 06. 10. 2015 Date of issue: 20. 06. 2007 Page: 8/(13)

pH: not applicable

9.2 Other information

No data available.

Section 10 Stability and reactivity

10.1 Reactivity: Dangerous reactivity not known.

10.2 Chemical stability: No decomposition if stored and handled properly.

10.3 Possibility of hazardous

reactions: Not known.

10.4 Conditions to avoid: Direct heat or ignition sources.

10.5 Incompatible materials: Strong oxidizing agents.

10.6 Hazardous decomposition No dangerous decomposition products are formed under normal

products: conditions. Hazardous combustion products: See Section 5.

Section 11 Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

Oral: LD_{50} (rat) > 2000 mg/kg (based on components) Dermal: LD_{50} (rabbit) > 2000 mg/kg (based on components)

Acute toxicity: irritation

Skin: not irritant (based on components)

Note: Prolonged and/or repeated contact may cause irritation on skin depending

on individual sensitivity

Eye: irritant (based on components), causes serious eye damage.

Respiratory or skin sensitisation: sensitising (based on components)

Other information, specific effects:

The product does not contain PCBs, PCTs, and other chlorine compounds, and heavy metals, barium compounds.

Note L: The classification as a carcinogen need not apply according to 1272/2008/EC, because it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

Germ cell mutagenicity: not known, resp. not mutagen (based on components)

Carcinogenicity: not known, resp. not carcinogen (based on

components)





Trade name: MOL Hykomol LS 85W-90 limited slip gear oil

Version: 4 Latest revision: 06. 10. 2015 Date of issue: 20. 06. 2007 Page: 9/(13)

Reproductive toxicity: not known, resp. no reproduction-damaging effect

(based on components)

STOT-single exposure: not known STOT-repeated exposure: not known Aspiration hazard: not known

Section 12 Ecological information

12.1 Toxicity No data for the product.

Aquatic organisms: Soil organisms:

Plants:

12.2 Persistence and degradability No data available.

Biodegradability: No data available.

12.3 Bioaccumulative potential No data available.

12.4 Mobility

Mobility in soil Absorbs in soil.

Mobility in water: Floats on water.

12.5 Results of PBT and vPvB Does not contain PBT and vPvB substances.

assessment

12.6 Other adverse effects

Heavy metal content: None. PCT, PCB and other chlorinated None.

hydrocarbons:

Environmental effects: Harmful to aquatic life with long lasting effects.

Water hazard class (German): WGK 2 (Classification by VwVwS)

Section 13 Disposal considerations

13.1 Waste treatment methods

Product disposal:

Wastes of the product or used oil should be treated as hazardous waste.

Waste Identification Code: 13 02 05*

Mineral-based non-chlorinated engine, gear and lubricating oils.

Disposal must be in compliance with national and local regulations.

Recommended waste treatment method: incineration



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Hykomol LS 85W-90 limited slip gear oil

Version: 4 Latest revision: 06. 10. 2015 Date of issue: 20. 06. 2007 Page: 10/(13)

Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

Waste Identification Code: 15 01 10*

Packaging containing residues of or contaminated by dangerous substances.

Disposal must be in compliance with national and local regulations.

Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

Care should be taken in any case to ensure compliance with EC, national and local regulations. It is the responsibility of the user to know all relevant national and local regulations.

Section 14 Transport information

Land transport:

Road/ Railway ADR/RID: Not classified.

14.1. UN number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards:

14.6. Special precautions for user:

Waterways:

Inland waterways/ Sea transport ADN/IMDG: Not apply to the product.

Air transport: ICAO / IATA: Not apply to the product.

Section 15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the mixture. This safety data sheet has been prepared according to Regulation (EC) No 1907/2006 (applicable version) and to Regulation (EC) 1272/2008.
- 15.2 Chemical safety assessment.

Not available.





Trade name: MOL Hykomol LS 85W-90 limited slip gear oil

Version: 4 Latest revision: 06. 10. 2015 Date of issue: 20. 06. 2007 Page: 11/(13)

Section 16 Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use. The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.

Source of data presented in this material safety data sheet:

Test results of this product

Material safety data sheets of product's components

Hungarian and EU lists of dangerous substances

Relevant Hungarian regulation and EU directives

Classification for mixtures and used evaluation method according to regulation

1272/2008/EC (CLP)

Skin Sens. 1 H317 calculated method Eye Dam. 1 H318 calculated method Aquatic Chronic 3 H412 calculation method

The full text of each relevant Hazard classes and cat., H- phrase in Section 3.:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Hykomol LS 85W-90 limited slip gear oil

Version: 4 Latest revision: 06. 10. 2015 Date of issue: 20. 06. 2007 Page: 12/(13)

Flam.Liq. 3 Flammable liquid Category 3
Acute Tox. 4 Acute toxicity Category 4
Asp.Tox.1 Aspiration hazard Category 1

Skin Corr. 1C Respiratory/skin sensitization Category 1C Skin Irrit. 2 Skin corrosion/irritation Category 2
Skin Sons 1 Respiratory/skin sensitization Category 1

Skin Sens. 1 Respiratory/skin sensitization Category 1 Eye Dam. 1 Serious eye damage/eye irritation Category 1

STOT SE 3
Specific target organ toxicity – single exposure Category 3
STOT RE 2
Aquatic Acute 1
Aquatic Chronic 1
Aquatic Chronic 2
Aquatic Chronic 3
Aquatic Chronic 3
Specific target organ toxicity – repeated exposure Category 2
Hazardous to the aquatic environment, Acute Category 1
Hazardous to the aquatic environment, Chronic Category 2
Hazardous to the aquatic environment, Chronic Category 3

Legend:

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE Acute Toxicity Estimate
BCF Biocontrentration Factor
BOD Biological Oxigen Demand

Bw Body Weight

C&L Classification and Labeling CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

CMR Carcigonic, Mutagenic or toxic to Reproduction

COD Chemical Oxygen Demand
CSA Chemical Safety Assessment
CSR Chemical Safety Report
DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
ECHA European Cheamicals Agency
Ecx Effective Concentration x%

Edx Effective Dose x%

ELINCS European List of Notified Chemical Substances ErC50 EC50 in terms of reduction of growth rate;

ES Exposure Scenario

ESIS European Chemical Substances Information System IARC International Agency for Research on Cancer



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Hykomol LS 85W-90 limited slip gear oil

Version: 4 Latest revision: 06. 10. 2015 Date of issue: 20. 06. 2007 Page: 13/(13)

IATA International Air Transport Association	
IATA International Air Transport Association IMDG International Maritime Dangerous Goods	
LCx Lethal Concentration x%	
LDx Lethal Dose x%	
LOAEC Lowest Observed Adverse Effect Concentration	
LOAEL Lowest Observed Adverse Effect Level	
LOEC Lowest Observed Effect Concentration	
LOEL Lowest Observed Effect Level	
NOEC No observed effect concentration	
NOEL No observed effect level	
NLP No-Longer Polymer	
NOAEL No Observed Adverse Effect Level	
OECD Organisation for Economic Cooperation and Development	
PBT Persistent Bioaccumulative and Toxic	
PNEC Predicted No-Effect Concentration	
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals	
RID Regulations concerning the International Carriage of Dangerous Goods b	by Rail
SVHC Substance of Very High Concern	
UVCB substance of unknown or variable composition, complex reaction produc materials	ets or biological
VOC Volatile organic compounds	
vPvB Very Persistent and very Bio-accumulative	

Revision Indicators:

Section	Subject of change	Date	Version
2	Hazards identification	26.08.2013	2
3	Composition/information on ingredients		
8	Exposure controls / personal protection		
9	Physical and chemical properties		
11	Toxicological information		
1-16	Revision modification according to 1272/2008/EC and		
	453/2010/EC		
2	Hazards identification	17.11.2014	3
3	Composition/information on ingredients		
1-16	Regulatory information and other corrections		
1	Details of the supplier of the safety data sheet,	06.10.2015	4
	Responsible for SDS		
3	Composition/information on ingredients		
9	Physical and chemical properties		
1-16	Other corrections, revision modification according to		
	2015/830 /EU		