

# MOL EcoClean-W

## engine degreaser



MOL EcoClean-W is a water based degreasing liquid containing a high quantity of active ingredients.

### Application:

- Use a strong water jet to wash the surface to be treated.
- Apply the product on the surface to be treated by means of brushing, spraying or immersing.
- It will loosen or dissolve the contamination of the surface during 15-20 minutes of soaking.
- Then use strong water jet again to remove the contamination from the surface. If the surface is heavily contaminated, it is recommended to use repeated soaking and washing.

Do not exceed the recommended soaking time for painted or lacquered surfaces, because the coating may get damaged.

## Application



- Cleaning of vehicle surfaces contaminated with oil, grease or bitumen
- Cleaning of railway tank wagons and underground tanks
- Cleaning of plant floors and tile surfaces
- Degreasing sheets treated with temporary preventive oil, prior to machining

## Features and benefits

- |                                     |  |
|-------------------------------------|--|
| Optimized active ingredient content | Efficiently removes even the most tenacious deposits       |
| Solvent-free composition            | Safe application, even in the presence of ignition sources |

## Properties

Properties	Typical values
Appearance	yellow, free of sediments
pH value	8,1
Density at 15 °C [g/cm3]	1,02

The characteristics in table are typical values of the product and do not constitute a specification.

## Storage and handling instructions

Should be stored in its original packaging with airtight sealing, separately from foods, in a place protected against water and sunshine, locked away from children.

In the original container under the recommended storage conditions: 24 months

Recommended storage temperature: +5°C - +35°C